

YUMAX[®] P-305LT

Premium Quality
Rust Preventative

PRODUCT DATA SHEET

GENERAL DESCRIPTION:

YUMAX[®] P-305LT is a solvent based type, barium free, rust preventive formulated to provide excellent corrosion protection for 1-2 months of indoor storage. YUMAX[®] P-305LT is an excellent choice for rust protection of in-process parts during short to medium term indoor storage. YUMAX[®] P-305LT has excellent water displacing properties and will not stain metal parts.

BENEFITS:

- EXCELLENT CORROSION PROTECTION – FOR 1-2 MONTHS
- BARIUM FREE
- NON-STAINING THIN PROTECTIVE FILM
- EXCELLENT WATER DISPLACING CLEANER
- EFFECTIVE PROTECTION FOR COPPER ALLOYS
- EASILY REMOVED WITH YUMAGE CLEANERS
- LOW ODOR

PROPERTIES:

Film Type	Oily
Non Volatile (110°C, 1hr)	13 wt. %
Specific Gravity (15°/15°C)	0.81
Color (ASTM)	L2.5
Film Thickness	1-2 Microns
Viscosity	2.6 mm ² /s @ 40°C
Appearance	Light Brown Liquid

USING PROCEDURES:

YUMAX[®] P-305LT is to be used full strength for best results. Typically, parts are dipped into a tank containing YUMAX[®] P-305LT to completely coat all exposed surfaces. A drain plug should be located in the bottom of the tank to facilitate the regular draining of water.

MATERIAL SAFETY:

Safe on ferrous and non-ferrous metals.

CONCENTRATION CONTROL:

Not applicable.

STORAGE:

Store in a cool dry area, away from heat and open flames.

PRECAUTIONS:

Please refer to the label and Materials Safety Data Sheet for all warnings, recommendations for safety equipment and other regulatory information.

AVAILABILITY:

Pails, Drums, Totes, Bulk