

YUMAX® P-307
Premium Quality
Rust Preventative

PRODUCT DATA SHEET

GENERAL DESCRIPTION:

YUMAX® P-307 is a solvent based rust preventative formulated to provide corrosion protection during shipping and for up to six (6) months of indoor storage. **YUMAX® P-307** is typically used to protect in-process and finished parts that may be stored for long periods. **YUMAX® P-307** exhibits excellent water displacing characteristics and will not stain metal parts.

BENEFITS:

- **EXCELLENT CORROSION PROTECTION - UP TO 6 MONTHS**
- **NON-STAINING PROTECTIVE FILM**
- **EXCELLENT WATER DISPLACING CHARACTERISTICS**
- **EASILY REMOVED WITH YUMAGE CLEANERS**

PROPERTIES:

Film Type.....	Oily
Non Volatile.....	45 wt%
Specific Gravity (15/4 °C).....	0.88
Color (ASTM).....	8.0
Film Thickness.....	6-7 Microns
Viscosity.....	4.4 mm ² /s @ 40 °C
Flash Point (PMCC).....	40 °C
Appearance.....	Brown Liquid

USING PROCEDURES:

YUMAX® P-307 is to be used full strength for best results. Typically, parts are dipped into a tank containing **YUMAX® P-307** to completely coat all exposed surfaces. A drain plug should be located in the bottom of the tank to facilitate the regular draining of water.

MATERIAL SAFETY:

Safe for use on ferrous metals or as directed.

CONCENTRATION CONTROL:

Not applicable

STORAGE:

Store in a cool dry area.

PRECAUTIONS:

Please refer to the label and Material Safety Data Sheet for all warnings, recommendations for safety equipment, and other regulatory information.

AVAILABILITY:

Pails, Drums, Totes, Bulk