

PRODUCT DATA SHEET

GENERAL DESCRIPTION:

YUMAX® P-352 is a solvent based rust preventive formulated to provide excellent corrosion protection for up to 1 month of indoor storage. **YUMAX® P-352** is an excellent choice for rust protection of in-process parts during short to medium term indoor storage.

YUMAX® P-352 has excellent water displacing properties and will not stain metal parts.

BENEFITS:

- **EXCELLENT CORROSION PROTECTION - UP TO 1 MONTH**
- **NON-STAINING THIN PROTECTIVE FILM**
- **EXCELLENT WATER DISPLACING CLEANER**
- **EFFECTIVE PROTECTION FOR COPPER ALLOYS**
- **EASILY REMOVED WITH YUMAGE CLEANERS**

PROPERTIES:

Film Type.....	Oily
Non Volatile (110°C, 1hr).....	18wt. %
Specific Gravity (15 ^o /15 ^o C)	0.81
Color (ASTM)	L3.5
Film Thickness	1-2 Microns
Viscosity	2.7 mm ² /s @ 40°C
Appearance	Light Brown Liquid

USING PROCEDURES:

YUMAX® P-352 is to be used full strength for best results. Typically, parts are dipped into a tank containing **YUMAX® P-352** to completely coat all exposed surfaces. A drain plug should be located in the bottom of the tank to facilitate the regular draining of water.

MATERIAL SAFETY:

Safe on ferrous and non ferrous metals.

CONCENTRATION CONTROL:

Not applicable.

STORAGE:

Store in a cool dry area, away from heat and open flames.

PRECAUTIONS:

Please refer to the label and Materials Safety Data Sheet for all warnings, recommendations for safety equipment and other regulatory information.

AVAILABILITY:

Pails, Drums, Totes, Bulk